

BATTERY-OPERATED GREASE-GUN 20V PUSH TYPE GREASE GUNS



015-3180-000

Battery-operated grease-gun 20V Li-Ion, suitable for 400g standard and screw Lube-Mec cartridges

The **display** indicates:

Battery level, grease level, amount of grease dispensed and no. cycles. The charger is protected against overload (charging time approx. 100% in 60 min. / 80% in 30 min.)

Fully charged battery dispenses up to 12 grease cartridges in conditions of free exit.

The plastic carry-along case has a space designed for an additional battery

Battery-operated grease-gun 20V Li-Ion

| Article | Capacity | Max pressure | Max delivery | Battery |
|--------------|----------|--------------|--------------|------------|
| 015-3180-000 | 500 g | 690 bar | 85 g/min | 20V Li-Ion |

Equipped with:

Plastic carry-along case

Battery operated grease-gun 20V Li-Ion

1000 mm flexible hose with 4-jaws coupler

Art. **015-3185-000** Multi purpose wide range input charger (12-240 V/ 50-60 Hz)

Art. **015-3186-000** Li-Ion battery 20V - 2000 mAh

Shoulder strap

It is suitable for 400 g cartridges Ø 52 mm



| | | | |
|--------------|-------|-------|---|
| 015-3180-000 | 6,130 | 0,010 | 1 |
|--------------|-------|-------|---|



015-3185-000

015-3186-000



Steel push type grease gun with Zerck coupler

| Article | Capacity | Diameter | Length | Max pressure |
|--------------|----------|----------|--------|--------------|
| 015-3305-050 | 50 g | 30 mm | 160 mm | 100 bar |
| 015-3310-200 | 200 g | 45 mm | 220 mm | 100 bar |



015-3305-050

Push type gun for high pressure grease, telescopic hose with Zerck coupler for spherical head and Lub for concave head

| Article | Capacity | Diameter | Length | Max pressure |
|--------------|----------|----------|------------|--------------|
| 015-3320-080 | 80 g | 37 mm | 150<220 mm | 200 bar |
| 015-3320-150 | 150 g | 37 mm | 220<350 mm | 200 bar |
| 015-3320-300 | 300 g | 47 mm | 260<430 mm | 200 bar |



015-3320-150

Push type grease gun for the filling of centralized lubrication systems of trucks, agricultural and construction machinery

| Article | Capacity | Diameter | Length | Max pressure |
|--------------|----------|----------|--------|--------------|
| 015-3350-000 | 500 g | 57 mm | 280 mm | 200 bar |

Manual and cartridge loading Ø 52 mm 400 g



015-3350-000